

LIFTING EQUIPMENT

KLP SERIES LEVER CHAIN HOIST

- High impact gear case and brake cover for heavy duty service
- Caged ball bearings on load sprocket for the ultimate in smooth, easy operation
- Dual pawl Weston-style brake features extra heavy pawl springs for reliable and safe operation
- Exclusive premium grade, non-asbestos brake discs for longest life
- Top and bottom safety hooks bend to warn of overloads
- Cast steel safety latches exceed industry standards
- Deformation indicators on hooks allow accurate measurement for easy maintenance
- Load tested to 150% of rated capacity with certificate
- Standard(s) Met: ISO 9001-2000, ASME B30.21
- Load Chain Grade: 100
- Number of Falls: 1
- Force Required to Lift: 46 lbs.
- Lever Length: 16-1/4"



Model No.	Mfg. No.	Capacity lbs. (tons)	Lift'	Load Chain Diameter	Min. Distance Between Hooks"	Price /Each
UAV860	110403	3000 (1.5)	5	7.1 mm	13-3/4	

KLP SERIES HEAVY-DUTY LEVER CHAIN HOIST

- High impact gear case and brake cover for heavy duty service
- Grade 100 load chain for greater strength
- Caged ball bearings on load sprocket for the ultimate in smooth, easy operation
- Dual pawl Weston style brake features extra heavy pawl springs for reliable and safe operation
- Exclusive premium grade, non-asbestos brake discs for longest life
- Top and bottom safety hooks bend to warn of overloads
- Cast steel safety latches exceed industry standard
- Deformation indicators on hooks allow accurate measurement for easy maintenance
- Load tested to 150% of rated capacity (with certificate)
- Meets ASME B30.21 standards



Model No.	Mfg. No.	Capacity lbs. (tons)	Lift'	Load Chain Diameter	Min. Distance Between Hooks"	Price /Each
UAV892	110404	6000 (3)	5	10 mm	16-1/2	
UAV893	110406	1500 (0.75)	10	5.6 mm	11	

KLP SERIES HEAVY-DUTY LEVER CHAIN HOIST WITH OVERLOAD PROTECTION

- High impact gear case and brake cover for heavy duty service
- Grade 100 load chain for greater strength
- Caged ball bearings on load sprocket for the ultimate in smooth, easy operation
- Dual pawl Weston style brake features extra heavy pawl springs for reliable and safe operation
- Exclusive premium grade, non-asbestos brake discs for longest life
- Top and bottom safety hooks bend to warn of overloads
- Cast steel safety latches exceed industry standard
- Deformation indicators on hooks allow accurate measurement for easy maintenance
- Load tested to 150% of rated capacity (with certificate)
- Meets ASME B30.21 standards
- Complete with automatic overload protection
- Overload clutch prevents application of overloads severe enough to damage puller or present a danger to workers



Model No.	Mfg. No.	Capacity lbs. (tons)	Lift'	Price /Each
UAV894	110414	6000 (3)	5	

VLP SERIES LEVER CHAIN HOIST

- Cold formed stamped steel housings resist impact
- Hardened steel roller bearings support load for easier operation
- Dual pawl Weston-style brake for reliable and safe operation
- Exclusive premium grade, non-asbestos brake discs for longest life
- Top and bottom safety hooks bend to warn of overloads
- Deformation indicators on hooks allow accurate measurement for easy maintenance
- Load tested to 150% of rated capacity with certificate
- Lift: 10'
- Standard(s) Met: ISO 9001-2000, ASME B30.21
- Load Chain Grade: 80
- Number of Falls: 1



Model No.	Mfg. No.	Capacity lbs. (tons)	Load Chain Diameter	Min. Distance Between Hooks"	Force Required to Lift lbs.	Lever Length"	Price /Each
UAV857	110306	1653.46 (0.75)	6 mm	12	31	12	
UAV858	110307	3000 (1.5)	8 mm	15	48	16-1/2	
UAV859	110308	6600 (3)	10 mm	18-7/8	70	16-1/2	